



STANDALONE TIME ATTENDANCE AND ACCESS CONTROL SYSTEM

Fingerprints Templates : 3000
Transaction Storage : 30,000
Card Capacity : 3000
Card Reader : Inbuilt proximity card reader (optional Mifare)
CPU : 32 bit High End Microprocessor
Fingerprint sensor : 500 DPI Optical Sensor
FAR : $\leq 0.0001\%$ / FRR : $\leq 1\%$
Identification Speed : ≤ 1 sec
Algorithm Ver : 10
Display : 2.8" Color TFT
Keypad : Yes
Schedule Bell/Speaker : Mini Speaker
Communication : TCP/IP, USB, RS232 , RS485
Push Data : Standard
Standard Features : Work code, SMS, DLST, Self Service Query, Status Switch
Power Supply : DC 12 V , 1.5Amps
Operating Temperature : 0°C to 45°C
Operating Humidity : 20% - 80%
Dimension : 183 x 80 x 42mm

Access Control :

Wiegand : In & Out
Relay : 12V relay for lock EM lock, Bolt Lock or Strike lock
Support Fire Alarm : No / Door Sensor : Yes
Anti Pass back : yes / Door Bell : Yes
Support exit reader : FR 1200 / KR500
Battery : No / Card Readers : Yes

Compatibility :

- Compatible with Multi Door controllers via weigand
- External Speaker output available (Optional)
- External Bulb output available (Optional)

Compatible Software & SDK

SmartOffice
Time and Attendance Software

- Smart office suite desktop and web
- Smart office 365 cloud
- SDK for desktop applications
- Web based Device manager/ ePush server using push data. helps developers & integrators
- Supports 3rd party payroll/HRMS/ERP and other applications