



S990A



RFID



Access

STANDALONE RFID TIME ATTENDANCE AND ACCESS CONTROL SYSTEM

Card Capacity : 30000
Transaction Storage : 1,00,000
Card Reader : Inbuilt proximity card reader
(optional Mifare)
CPU : 800 Mhz 32 bit Microprocessor
Fingerprint sensor : 500 DPI Optical Sensor
FAR : $\leq 0.0001\%$ / FRR : $\leq 1\%$
Identification Speed : $\leq 0.5\text{sec}$
Algorithm Ver : 10
Display : 3" Color TFT
Keypad : Yes
Schedule Bell/Speaker : Mini Speaker
Communication : TCP/IP, USB, Rs232, RS485
(Optional : Wifi, GPRS, GPRS+GPS)
Push Data : Yes
(Support both static IP and domain server)
Standard Features : Work code, SMS, DLST,
Self Service Query, Status Switch
Power Supply : DC 12 V , 1.5Amps
Operating Temperature : 0°C to 45°C
Operating Humidity : 20% - 80%
Dimension : 210 x 157 x 40mm

Access Control :

Wiegand : In & Out
both 26 or 34 bit (With or without site code)
Relay : 12V relay for lock EM lock,
Bolt Lock or Strike lock
Support Fire Alarm : Yes / Door Sensor : Yes
Anti Pass back : yes / Door Bell : Yes
Support exit reader : Push Button, KR500
Battery : Optional

Compatibility :

- Compatible with Multi Door controllers via weigand
- External Speaker output available (Optional)
- External Bulb output available (Optional)
- Support External Printer

Compatible Software & SDK

SmartOffice
Time and Attendance Software

- Smart office suite desktop and web
- Smart office 365 cloud
- SDK for desktop applications
- Web based Device manager/ ePush server using push data. helps developers & integrators
- Supports 3rd party payroll/HRMS/ERP and other applications