



FLB-162

TECHNICAL SPECIFICATION

Passage width	≥ 550 mm
Throughput rate	35 p/m
Power Supply	100-240 V/(ac)
Operational Voltage	24 V/(dc)
Max Power Consumption	35 W
Frequency	50-60 hz
Protection level	>44 IP
Working Temperature	-25° ~ 70°
Dimension excluding bars	1410 x 340 x 1005 mm
Net weight including bars	75 kg

MATERIALS

- Housing: Made in stainless steel AISI 304 or AISI316
- Barrier swings-acrylic, PC, stainless steel frame

OPERATING MODES

- Single passage in the set direction
- Bi-Directional single passage
- Free passage in the set direction
- Always free or locked

FEATURES AND BENEFITS

- A direction indicator, showed that pedestrian access to the current status of, and guide pedestrians correct and smooth passage
- Display has been in use for statistics and numbers
- With voice and strobe light alerts
- A combination of infrared sensors and police antillegal entry into pedestrian access, the protection of pedestrians smooth and the prevention of the channel following
- Double anti-clipping function , photocell antic lipping and mechanical anti-clipping
- Auto reset function, if no passing during identified card reading time, the system will reset automatically the passengers are prohibited to pass until their second identifies reading
- The barrier can be set to delay closing in 1-60s after a valid card reading