



## N-SC403 Beat The Biometrics



RFID



Password



LAN



Mini USB



Access Control

## RFID Attendance and Access Control

### Storage Capacity

Card Capacity	30,000
Max User	30,000
Password	30,000
Log Capacity	1,60,000



### Features

RFID & Password Identification

Accepting Card from 1 to 5 cm.

Less than 1 sec. card reading speed.

Supremely low Electric energy consumption.

Highly reliable and durable.

Comprehensive software development kit(SDK) is available for development and integration.

# N-SC403

## Communication Interface

Communication	TCP/IP & Mini USB
---------------	-------------------

## Biometric

Push Data	No
FAR	0.00001%
FRR	0.001%
CPU	High speed industrial processor
Verification Time	<=1 second
RF card options	125kHz EM / 13.56MHz Mifare (Optional)

## Audio/Visual

LCD	2.4" TFT color screen
Voice instruction	16-bit Hi-Fi voice & sound indication
Language	English

## Access control

Relay	YES
Support Reader	RS485 Reader, Bell, Wiegand Reader, Wireless Remote, Push Button, No Touch Sensor.

## Power & Environment

Operating Temperature	0°C ~ 50°C
Power	12V DC / 2A
Dimension (L*H*W)	95 x 125 x 45 mm



TCP/IP, Mini USB



Unaffected by High  
Temperatures 0° ~ 50°



Highly reliable & durable.

Desktop based Software



Time Attendance



Access Control

**Disclaimer** : Brief specifications are mentioned here. specification may change without prior notice. Customers are advised to check with us before purchase. Actual product may differ slightly to that depicted for ongoing product development.

Certified by   CE FC

[www.biomaxsecurity.com](http://www.biomaxsecurity.com)

Connect with us on



BiomaxOfficial



BioMax Security



biomaxsecurity



BioMax Access Control