



N-Uface302 Pro Multi Bio



















Face

Finger

RFID

(Optional)

Wi

LAN

USB

GPRS (Optional

Access

Multi-Bio Attendance and Access Control

Storage Capacity

Face Capacity	3000
Finger Capacity	10,000
Card Capacity	3000
Max Users	3000
Log Capacity	2,00,000

Features

High-Speed and Accurate Face Identification

Good adaptation for dry, moist and rough fingerprints.

Output relay for door open.

Face, Fingerprint, Card, Password authentication

Supremely low Electric energy consumption.

Highly reliable and durable.

Comprehensive SDK is available for development and integration.




N-Uface302

Communication Interface

Communication	WIFI, TCP/IP, RS 485, USB
---------------	---------------------------

Biometric

2.00	
Push Data	Yes
4G GPRS	Yes (Optional)
GPS	Optional
Sensor type	500 DPI
FAR	0.00001%
FRR	0.001%
Processor	1 GHz
OS	Linux
Verification time	<= 1 second
RF card options	125kHz EM (Standard) /
	13.56MHz Mifare (Optional)



Audio/Visual

LCD	2.8" TFT color screen
Voice instruction	16-bit Hi-Fi voice & sound indication
Language	English

Software Desktop, Web, Cloud

Access control

Wiegand in & out	YES
Relay	YES
Rs485	Finger & Card Reader
Support	RS485 Reader, Wiegand Reader,
	Remote Push Button, No Touch



Time Attendance



Access Control



Employee Self Service



Mobile App

Power & Environment

Battery	Yes (Optional)
Operating Temperature	0°c ~ 50°c
Power	12V DC / 2A
Dimension (L*H*W)	175 x 120 x 95 mm

Disclaimer: Brief specifications are mentioned here. specification may change without prior notice. Customers are advised to check with us before purchase. Actual product may differ slightly to that depicted for ongoing product development.

Connect with us on







