



## V-AX18

Safe Guard in Style



Finger



RFID



Battery (Optional)



LAN



USB



Access Control



Feather Touch Keypad

## Fingerprint Time Attendance and Access Control

### Storage Capacity

Finger Capacity	3000
Card Capacity	3000
Max Users	3000
Password	3000
Log Capacity	1,00,000

### Features

High-Speed and Accurate Fingerprint Identification  
Fingerprint, Card, Password authentication  
output relay for door open.

Good adaptation for dry, moist and rough fingerprints.

Supremely low Electric energy consumption.

Highly reliable and durable.

Comprehensive software development kit(SDK) is available for development and integration.



# V-AX18

## Communication Interface

Communication	TCP/IP, RS485, USB Host & Client
---------------	----------------------------------

## Biometric

Push Data	YES
Sensor type	500 DPI
FAR	0.00001%
FRR	0.001%
SSR	YES
Verification time	<=1 second
RF card options	Mifare Card (Optional)
Memory	512MB



Accepts moist and rough Finger



Accepts Color & Mahendi Finger



Compact & lightweight design



Unaffected by High Temperatures -20°C ~ 50°C

## Audio/Visual

LCD	2.8" Color Screen
Voice instruction	16-bit Hi-Fi voice & sound indication
Language	English

## Access control

Relay	YES
Support	V-R12, Wiegand Reader, Push Button, Remote, No Touch

## Power & Enviroment

Battery Backup	YES (Optional)
Operating Temperature	-20°C ~ 50°C
Power	DC 12V, 2Amp
Dimension	83.9 x 204.9 x 31mm

### Software

Desktop, Web, Cloud



Time Attendance



Access Control



Employee Self Service






Mobile App

**Disclaimer :** Brief specifications are mentioned here. specification may change without prior notice. Customers are advised to check with us before purchase. Actual product may differ slightly to that depicted for ongoing product development.

Certified by    

[www.biomaxsecurity.com](http://www.biomaxsecurity.com)

### Connect with us on

 BiomaxOfficial  BioMax Security  
 biomaxsecurity  BioMax Access Control