



Fingerprint Time Attendance System

Storage Capacity

Finger Capacity	3000
Card Capacity	3000
Max Users	3000
Password	3000
Log Capacity	1,00,000

Features

- High-Speed and Accurate Fingerprint Identification
- Fingerprint, Card, Password authentication
- Good adaptation for dry, moist and rough fingerprints.
- Supremely low Electric energy consumption.
- Highly reliable and durable.

Comprehensive software development kit(SDK) is available for development and integration.



V-TA45

Communication Interf	ace		
Communication	TCP/IP, Mini USB, USB Host & Client	Accepts moist and rough Finge	
Biometric			
Push Data	YES		
Sensor type	500 DPI	Accepts Color & Mahendi Finge	
FAR	0.00001%		
FRR	0.001%	Compact & lightweight design	
Verification time	<=1 second	:c	
SSR	YES		
Self-defined Status	YES	[]= Unaffected by High	
		Temperatures -20°C ~ 50°C	
Audio/Visual		Software	
LCD	2.8" Color Screen	Desktop, Web, Cloud	
Language	English		
Power & Enviroment		Time Attendance	
Battery Backup	YES (Optional)	Employee Self Service	
Operating Temperature	-20°C - 50°C		
Power	DC 5V, 1Amp		
Dimension	130x140x30mm	Mobile App	

Disclaimer : Brief specifications are mentioned here. specification may change without prior notice. Customers are advised to check with us before purchase. Actual product may differ slightly to that depicted for ongoing product development.

Connect with us on

(f) BiomaxOfficial biomaxsecurity BioMax Security

(in) BioMax Access Control



www.biomaxsecurity.com