



N-BM30W

DYNAMIC FEATURES IN ONE



Finger



RFID



Inbuilt Battery



WiFi



LAN



USB



Access Control

Time Attendance and Access Control

Storage Capacity

Finger Capacity	3000
Card Capacity	3000
Max User	3000
Password	3000
Log Capacity	1,50,000



Features

High-Speed and Accurate Fingerprint Identification

Fingerprint, Card, Password authentication

output relay for door open.

Good adaptation for dry, moist and rough fingerprints.

Supremely low Electric energy consumption.

Highly reliable and durable.

Comprehensive software development kit(SDK) is available for development and integration.

N-BM30W

Communication Interface

Communication	WiFi, TCP/IP, USB
---------------	-------------------

Biometric

Push Data	YES (Optional)
Sensor type	500 DPI
FAR	0.00001%
FRR	0.001%
CPU	Industrial High Speed CPU
Verification Time	<=1 second
RF card options	125kHz EM (Standard) / 13.56MHz Mifare (Optional)

Audio/Visual

LCD	2.4" TFT color screen 320x240 pixel
Voice instruction	16-bit Hi-Fi voice & sound indication
Language	English

Access control

Wiegand in & out	YES
Relay	YES
Support Exit Reader	Wiegand Reader, Remote, Push Button, No Touch

Power & Environment

Inbuilt Battery Backup	YES
Operating Temperature	0°C ~ 50°C
Power	12V DC / 2A
Dimension	160 x 150 x 65 Pixels



Accepts moist and rough Finger



Accepts Color & Mahendi Finger



WiFi, TCP/IP, USB



Unaffected by High
Temperatures 0° ~ 50°

Software

Desktop, Web, Cloud



Time Attendance



Access Control



Employee Self Service



Mobile App

Disclaimer : Brief specifications are mentioned here. specification may change without prior notice. Customers are advised to check with us before purchase. Actual product may differ slightly to that depicted for ongoing product development.

Connect with us on



BiomaxOfficial



BioMax Security



biomaxsecurity



BioMax Access Control