



SPEEDFACE - 5 SE



Face



Masked
Face



Live Body
Detection



QR
Code



RFID
Mifare



WiFi



TCP/IP



Access
Control

Facial Attendance and Access Control

Storage Capacity

Face Capacity	6000
Card Capacity	6000
QR Capacity	6000
Max User	6000
Log Capacity	2,00,000



Features

5-inch capacitive touch screen

DualCoreARM Cortex-A7 Processor

Remotely Firmware Upgradation.

Detect 5 person at a time

5-inch TN display all-sight LCD touch screen with 480*854 resolution.

IP54 Grade Highly finished slim device.

Highly reliable and durable

Recognition speed 0.5 seconds

SpeedFace - 5 SE

Communication Interface

Communication	Wi-Fi, TCP/IP, USB
---------------	--------------------

Biometric

Push Data	Yes
Remote firmware update	Yes
FAR	0.001%
Accuracy ratio	99.27%
Processor	Dual Core ARM Cortex-A7
OS	Linux
Verification time	<=1 second
Mifare card	Yes

Audio/Visual

LCD	5.0" TN touch screen display
Shutter type	Electronic Rolling Shutter
Language	English

Access control

Wiegand out	Yes
Relay	Yes
Live Detection	Yes

Power & Environment

Operating Temperature	-10°C ~ 50°C
Power	12V DC / 2A
Dimension	185.8 x 93.7 x 22.5 mm



Auto Focus



Autofill light



Long Distance Verification

Software

Web & Cloud



Time Attendance



Access Control



Employee Self Service



Mobile App

Disclaimer : Brief specifications are mentioned here. specification may change without prior notice. Customers are advised to check with us before purchase. Actual product may differ slightly to that depicted for ongoing product development.

Certified by



www.biomaxsecurity.com

Connect with us on



BiomaxOfficial



BioMax Security



biomaxsecurity



BioMax Access Control