



## SPEEDFACE - 5 THRL



Face



Temperature  
Detection



Live Body  
Detection



Touch  
Screen



WiFi



LAN



Access  
Control

## Facial Attendance and Access Control

### Storage Capacity

Face ID Capacity	50,000
Card Capacity	50,000
Log Capacity	2 00 000

### Features

Industrial grade design with stable performance & smooth line

5-inch IPS display all-sight LCD touch screen.

Dual core ARM cortex - A7 @900MHz Processor

Detect human body temperature through face

Recognition speed 0.5 seconds



Speed Face - 5 THRL

"Advance Infrared  
temperature sensor."

# SpeedFace - 5 THRL

## Communication Interface

Communication	WIFI, TCP/IP
---------------	--------------

## Biometric

Push Data	YES
Remote firmware update	YES
FAR	0.001%
Accuracy ratio	99.27%
Processor	Dual Core ARM Cortex-A7 @900MHz
OS	Linux
Anti Backlight	YES
Verification time	<=1 second
Additional Feature	Temperature Detection Sensor

## Audio/Visual

LCD	5.0" IPS touch screen display
Screen Resolution	480 * 854
Camera Specification	2 MP
Shutter type	Electronic Rolling Shutter
Body Temperature display	YES

## Access control

Living body detection	YES
Relay	YES

## Power & Environment

Operating Temperature	-10°C -50°C
Environment for Temp Measurement	22°C~32°C
Temp Measurement Distance	30cm~120cm
Temp Measurement Environment	10°C~42°C
Temp Measurement Range	35.5°C~42°C (95.9°F~107.6°F)
Power	12V DC / 2A
Dimension	216.00 x 90 x 25 mm



Auto Focus



low light Verification



Detect Body Temperature

Software

Web & Cloud



Time Attendance



Access Control



Employee Self Service



Mobile App

**Disclaimer** : Brief specifications are mentioned here. specification may change without prior notice. Customers are advised to check with us before purchase. Actual product may differ slightly to that depicted for ongoing product development.

Certified by   

[www.biomaxsecurity.com](http://www.biomaxsecurity.com)

Connect with us on



BiomaxOfficial



BioMax Security



biomaxsecurity



BioMax Access Control