

SPEEDFACE - 5



Face



Touch
Screen



RFID



WiFi



LAN



USB



Access
Control

Facial Attendance and Access Control

Storage Capacity

Face ID Capacity	50,000
Card Capacity	50,000
Log Capacity	2,00,000



Features

DualCoreARM Cortex Processor

Remotely Firmware Upgradation.

5-inch IPS display all-sight LCD touch screen with 480*854 resolution.

IP54 Grade Highly finished slim device.

Highly reliable and durable

Recognition speed 0.5 seconds

SpeedFace - 5

Communication Interface

Communication	WIFI, TCP/IP, USB
---------------	-------------------

Biometric

Push Data	YES
Remote firmware update	YES
FAR	0.01%
FAR	0.01%
Accuracy ratio	99.99%
Processor	Dual Core ARM Cortex
OS	Linux
Verification time	<=1 second
RF card options	Wiegand 26/34

Audio/Visual

LCD	5.0" IPS touch screen display
Shutter type	Electronic Rolling Shutter
Language	English

Access control

Relay	YES
Wiegand output	YES

Power & Environment

Operating Temperature	-10°C ~ 50°C
Power	12V DC / 2A
Dimension	190.00 x 87.53 x 17.00 mm



Auto Focus



low light Verification



Long Distance Verification

Software

Web & Cloud



Time Attendance



Access Control



Employee Self Service







Mobile App

Disclaimer : Brief specifications are mentioned here. specification may change without prior notice. Customers are advised to check with us before purchase. Actual product may differ slightly to that depicted for ongoing product development.

Certified by   

www.biomaxsecurity.com

Connect with us on

 BiomaxOfficial  BioMax Security
 biomaxsecurity  BioMax Access Control