



SPEEDFACE - 8



Face



Live Body
Detection



Touch
Screen



RFID



WiFi



LAN



USB



Access
Control

Facial Attendance and Access Control

Storage Capacity

Face ID Capacity	1,00,000
Max User	1,00,000
Card Capacity	1,00,000
Log Capacity	2,00,000



Features

Industrial grade design, with stable performance & smooth line

IP66 protection grade.

8-inch IPS display all-sight LCD touch screen.

Dual core ARM cortex Processor

Highly reliable and durable

Recognition speed 0.5 seconds

SpeedFace - 8

Communication Interface

Communication	WIFI, TCP/IP, USB
---------------	-------------------

Biometric

Push Data	YES
Remote firmware update	YES
FAR	0.01%
Accuracy ratio	99.99%
Processor	Dual Core ARM Cortex
OS	Linux
Anti Backlight	YES
Verification time	<=1 second

Audio/Visual

LCD	8.0" IPS touch screen display
Screen Resolution	800 x 1280
Camera Specification	2 MP
Shutter type	Electronic Rolling Shutter

Access control

Living body detection	YES
Relay	YES

Power & Environment

Operating Temperature	-10°C ~ 50°C
Power	12V DC / 2A
Dimension	270 X 130 X 90 mm



Auto Focus



low light Verification



Long Distance Verification

Software

Web & Cloud



Time Attendance



Access Control



Employee Self Service



Mobile App

Disclaimer : Brief specifications are mentioned here. specification may change without prior notice. Customers are advised to check with us before purchase. Actual product may differ slightly to that depicted for ongoing product development.

Certified by   

www.biomaxsecurity.com

Connect with us on



BiomaxOfficial



BioMax Security



biomaxsecurity



BioMax Access Control